# **Protect All Genius Spray**

Revision: 5/02/2019 Page 1 from 1

#### **Technical data**

| Basis                            | Mixture based on silicone oil |
|----------------------------------|-------------------------------|
| Consistency                      | Liquid                        |
| Density**                        | Ca. 0,69 g/ml                 |
| Solubility in water              | Not soluble                   |
| Volatile Organic Compounds (VOC) | 76 %                          |
| Temperature resistance**         | -40 °C → 350 °C               |
| Application temperature          | 5 °C → 30 °C                  |

<sup>\*</sup> These values may vary depending on environmental factors such as temperature, moisture, and type of substrates. \*\* This information relates to fully cured product.

## **Product description**

Protect All Genius Spray is a transparent spray with lubricating and anti-adhesive characteristics based on high-grade silicone oil. Genius spray allows precise extrusion and regular spray action.

# **Properties**

- Lubricates
- Reduces friction and wear
- Rust and corrosion-resistant
- Water-repellent
- Electric insulating
- For in and outdoor use
- Aerosol can be used in any angle (360°)
- Contains non flammable propellant

# **Applications**

- Reduces friction and reduces wear on mechanical parts and is therefore suitable for light lubrication of metals, plastics and rubbers.
- Prevents dirt and grease deposits and is therefore ideally suited for rails.
- Creates a water-repellent layer and protects the electric wiring of cars, engines, lawn mowers, etc. from moisture.
- Gives plastics and rubber a glossy finish.
- Not to be used for brake drums and brake discs.
- Treated surfaces cannot be painted.
- Applicable within a wide temperature range.

# **Packaging**

Colour: transparent
Packaging: 300 ml aerosol

# Shelf life

3 years in unopened packaging in a dry and cool environment at temperatures between +5°C and +25°C.

#### **Substrates**

*Nature*: clean, free of dust and grease. All types of metals and plastics.

### **Application method**

Application method: Surfaces must be cleaned, degreased and dry. Shake can well before use. Spray at a distance of appr. 20 cm of the object. Apply a thin layer evenly.

### **Health- and Safety Recommendations**

Use only in well-ventilated areas. In case of contact with eyes, wash immediately with plenty of water.

### Liability

The content of this technical data sheet is the result of tests, monitoring and experience. It is general in nature and does not constitute any liability. It is the responsibility of the user to determine by his own tests whether the product is suitable for the application.